

easter PJs



correction

New instructions are on the following page.

pattern

The pj pattern is missing the centre fold line on the top front piece. It should be drawn 5.2cm in from the edge.

There are no notches on the collar to match the shoulder seam. They should be measured from the centre back fold line 4.2cm for size 2; 4.6cm for 3-4 and 5.1cm for size 5-6.

top

Cut out all pattern pieces and interfacing required.

Interfacing for front is cut to the fold line/interfacing line.

Fuse interfacing to upper collar piece and to wrong side of front pieces.

Finish (overlock or zigzag) the outer edges of the front pieces.

Staystitch neck edges. Stitch front and back sections together at shoulders. Stitch collar pieces together, leaving neck edge open. Trim corners and turn right side out and press.

Pin collar to right side of neck edge with upper collar facing out, matching centre back, notches to shoulder seams and ends of collar to centre front. Pin only under collar to neck edge between shoulder seams.

Fold front facings on fold line to right side over collar with edges of facings extending 1.5cm past shoulder seams. Stitch neckline through all layers the width of the facing, stitching only the under collar between shoulders, then through all layers the width of the facing on the other side. Trim corners and clip curves.

Turn facings to inside. Fold under seam allowance on upper collar and pin to neck edge covering stitches. Slip stitch closed. Slip stitch top of facings to shoulder seams.

Pin sleeve to armhole, right sides together. Stitch. Trim curves where necessary. Repeat for other sleeve.

Pin front to back, right sides together, at side seam and sleeve seam, matching underarm seams. Repeat for other side.

Fold over 6mm on bottom edge of sleeves and top and press. Fold over another 1.5cm (or required length), press and stitch.

Use the buttonhole function on your machine to make 3 buttonholes (on the left side), using the guide in the pattern lift-out to get the spacing right. Hand stitch the buttons in place on opposite front matching them with the holes.

Turn under 6mm on upper edge of pocket. Turn upper edge to outside along foldline and stitch ends. Trim off excess seam and turn right side out. Turn under remaining edges 6mm and press. Topstitch the pocket along the edge of the flap. Pin pocket on left hand side of top and stitch along the bottom and each side.

pants

As per magazine.